META GREASE



META Grease is premium quality calcium grease. It is suitable for variety of greasing applications in automotive, industrial, agriculture and marine machineries where temperature and loading conditions are moderate. META Grease is recommended for lubrication of various applications where a non EP grease is required.

PRODUCT FEATURES

- * Meta Grease is NLGI No. 3 grease containing non lead additives.
- * Good mechanical stability.
- * Excellent anti-wear, anti-rust and anti-corrosion properties.
- * Exceptional resistance to oxidation and water contaminations.
- * Used in centralized system due to good pumpability.
- * Excellent adhesion properties.

APPLICATION

META Grease provides long lasting durability in a broad range of applications where the temperature and loading conditions are normal. It is recommended for plain bearings, universal joints lubrication, nipples steering linkages and chassis suspension parts.

TECHNICAL SPECIFICATION

Characteristics	Units	Calcium Base
Color	-	Light Brown
Thickener	-	Calcium Soap
Extreme Pressure	-	NO
NLGI Grade	-	3
Dropping Point	°C	100
Base oil Viscosity @ 40°C	cSt	60
Water Solubility	-	Insoluble
Worked Penetration @25°C	mm/10	230-250
Operating Temperature Range	°C	-15 to +60

SPECIFICATIONS

ISO-L-XBCEA 2 DIN 51502 K2K 25

TYPES OF PACKING

Containers of: 0.5, 1, 15, 180Kg

MP₃ NLGI 3

SAFETY AND HANDLING

This lubricant is made of highly refined base oil and different types of additives. It does not constitute a special hazard or any toxic effects when used properly. Avoid contact with the skin. Prevent any splashing and keep away from combustible materials. Store properly under cover. Dispose off the used oil correctly.

LIVO LUBRICANTS E-mail: info@livo.us Website: www.livo.us